


Linear

LINI Glow XL R020

Fixture Guide

KKDÖ

Indoor | Surface | Output up to 1145lm/m (349lm/ft)




Key applications

- ✓ Architectural detail
- ✓ Cabinet & furniture
- ✓ Direct lighting
- ✓ Interior
- ✓ Mirror back lighting

Key features


- ✓ Custom lengths
- ✓ Constant Voltage (CV)
- ✓ Continuous light runs
- ✓ Diffusion: homogenous
- ✓ Direct view
- ✓ Extensive CCT range
- ✓ IP40 dry area
- ✓ IP44 moisture resistant



MOUNTING METHODS



KKCP-11 Concealed clip



KKCR-01-1000 Cable raceway (1000mm)
KKCR-01-2000 Cable raceway (2000mm)
KKCR-01-3000 Cable raceway (3000mm)



KKJT-02 Joining bar

Linear

LINE Glow XL R020

Specification sheet



Dimensions	H28/W22/L94-2011mm (H1.1/W0.87/L3.70-79.17in)
PCB Cut-point	41.7mm increment/2000mm max (1.64in increment/78.74in max)
LED Pitch	6.95mm-144LED/m (0.27in - 44LED/ft)
Chip	s-line k-line
Cover/Optics	Diffused (156°)
CCT	s-line: 1900K/2100K/2300K/2500K/2700K/3000K/3500K/4000K/5000K k-line: 1900K/2100K/2300K/2500K/2700K/3000K/3500K/4000K/5000K
LED binning	s-line: 2-step MacAdam ellipse k-line: 3-step MacAdam ellipse
CRI	≥ 92
Lifetime	50,000 hours @ 25°C (50,000 hours @ 77°F)
Operating temp	T _a = -25 to 50°C (T _c max = 71°C) T _a = -13 to 122°F (T _c max = 160°F)
IP Rating	IP40/IP44
Finish	Silver anodised
Mounting	Surface mounting via concealed clips or cable raceway
Power feed	Hardwire tails or male/female connectors
Control	0-10V/1-10V/DMX/DALI



LED Grading Key

Exclusive Grade



s s-line*	*KKDC tuned CCT range
2-step CCT range	

Base Grade

k k-line
3-step commercial range
Energy Star CCTs

Power consumption	Supply voltage	Supply current
20W/m (6.10W/ft)	24V DC	0.83A/m (0.25A/ft)

Diffused Cover		CRI	R9	Rf	Rg
s-line	1145lm/m (349lm/ft) 57.2lm/W	93	65	-	-
k-line	1080lm/m (329lm/ft) 54lm/W	92	64	-	-



— C0 / C180 cd / 1000 lm C90 / C270

Data derived from independent UKAS/IESNA LM-79-08 accredited testing of production samples.

LINI Glow XL R020

Code Table



FIXTURE

Model	Finish	Cover	Grade ¹	LED	Colour (CCT)	Length Availability ²	IP	Cable Length	Power Feed ³	Input	
LINI Glow XL	GX Silver Anodised	SA Diffused U cover	0 s- s k- k	R020 R020	1900K 19	m 94.3-2011mm 83.3mm increments i 3.71-79.17in 3.28in increments (Specify length code OR total run length)	IP40 40 IP44 44	300mm/ 11.81" 0300	Single no sheath tail Double no sheath tail Single no sheath IP20 connector Double no sheath IP20 connector	S00X D00X S20X D20X	DC 24V g
					2100K 21						
					2300K 23						
					2500K 25						
					2700K 27						
					3000K 30						
					3500K 35						
					4000K 40						
					5000K 50						

¹ Refer to **LED Grading Key** on **Specification sheet** page

² Refer to **Length Availability List** or enter total run length instead of length code

³ Refer to **Power Feed Options** on **Options** pages

Code Example:

GX	-	SA	-	0	-	s	-	R020	-	35	-	m	511	-	40	-	0300	-	D00X	-	g
LINI Glow XL		Silver Anodised		Diffused U cover				R020		3500K		511mm		IP40		300mm/11.81"		Double no sheath tail		DC 24V	

ACCESSORIES

Mounting Accessories

KKCP-11	Concealed Clip
KKCR-01-1000	1000mm/39.37" Cable Raceway
KKCR-01-2000	2000mm/78.74" Cable Raceway
KKCR-01-3000	3000mm/118.11" Cable Raceway
KKJT-02	Joining Bar (allow one per join)

* Refer to **Mounting accessories** on **Accessories** pages

Connection Accessories

KKCN-01	2 PIN male & female 50mm/1.97" pair
KKCN-03	2 PIN male & female 300mm/11.81" pair
KKCN-06	2 PIN 300mm/11.81" extension lead

* Refer to **Power feed** on **Accessories** pages

PSU/Driver

0-10V/1-10V/DALI/DMX

* Refer to **Driver/PSU Options** page for details or provide requirement and KKDC to offer the suitable option

LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	R007	386	118	7	2.13	LINI GLOW XL R007	94-2011mm (3.70-79.17in)	41.7mm (1.64in)
	R014	801	244	14	4.27	LINI GLOW XL R014	94-2011mm (3.70-79.17in)	41.7mm (1.64in)
	R020	1145	349	20	6.10	LINI GLOW XL R020	94-2011mm (3.70-79.17in)	41.7mm (1.64in)
Warm Dim/Dynamic White	A040	2680	817	40	12.19	LINI GLOW XL A040	88-1511mm (3.46-59.49in)	38.46mm (1.51in)
	R207	899	274	16	4.88	LINI GLOW XL R207	94-2011mm (3.70-79.17in)	83.3mm (3.28in)
RGB	501	Red: 90 Green: 193 Blue: 32 RGB: 280	Red: 27 Green: 59 Blue: 10 RGB: 85	15.6	4.75	LINI GLOW XL RGB	94-2011mm (3.70-79.17in)	83.3mm (3.28in)
RGBW	R201	689	210	20	6.10	LINI GLOW XL RGBW	136-2011mm (5.35-79.17in)	62.5mm (2.46in)

* Performance data: A-line, 3000K, diffused cover

LINI Glow XL R020

Length Availability List



Length Code		Fixture Length ¹		LED Strip ²		End Cap Dimension ³		Wattage (W)	Output (lm)
Metric	Imperial(US)	Metric	Imperial(US)	Metric	Imperial(US)	Metric	Imperial(US)		3000K (Test Data)
m0094	i0004	94mm	3.71in	83mm	3.28in	6mm	0.24in	1.67	90
m0136	i0005	136mm	5.35in	125mm	4.92in	6mm	0.24in	2.50	135
m0178	i0007	178mm	6.99in	167mm	6.56in	6mm	0.24in	3.33	180
m0219	i0009	219mm	8.64in	208mm	8.20in	6mm	0.24in	4.17	225
m0261	i0010	261mm	10.28in	250mm	9.84in	6mm	0.24in	5.00	270
m0303	i0012	303mm	11.92in	292mm	11.48in	6mm	0.24in	5.83	315
m0344	i0014	344mm	13.56in	333mm	13.12in	6mm	0.24in	6.67	360
m0386	i0015	386mm	15.20in	375mm	14.76in	6mm	0.24in	7.50	405
m0428	i0017	428mm	16.84in	417mm	16.40in	6mm	0.24in	8.33	450
m0469	i0018	469mm	18.48in	458mm	18.04in	6mm	0.24in	9.17	495
m0511	i0020	511mm	20.12in	500mm	19.69in	6mm	0.24in	10.00	540
m0553	i0022	553mm	21.76in	542mm	21.33in	6mm	0.24in	10.83	585
m0594	i0023	594mm	23.40in	583mm	22.97in	6mm	0.24in	11.67	630
m0636	i0025	636mm	25.04in	625mm	24.61in	6mm	0.24in	12.50	675
m0678	i0027	678mm	26.68in	667mm	26.25in	6mm	0.24in	13.33	720
m0719	i0028	719mm	28.32in	708mm	27.89in	6mm	0.24in	14.17	765
m0761	i0030	761mm	29.96in	750mm	29.53in	6mm	0.24in	15.00	810
m0803	i0032	803mm	31.60in	792mm	31.17in	6mm	0.24in	15.83	855
m0844	i0033	844mm	33.24in	833mm	32.81in	6mm	0.24in	16.67	900
m0886	i0035	886mm	34.88in	875mm	34.45in	6mm	0.24in	17.50	945
m0928	i0037	928mm	36.52in	917mm	36.09in	6mm	0.24in	18.33	990
m0969	i0038	969mm	38.16in	958mm	37.73in	6mm	0.24in	19.17	1035
m1011	i0040	1011mm	39.80in	1000mm	39.37in	6mm	0.24in	20.00	1080
m1053	i0041	1053mm	41.44in	1042mm	41.01in	6mm	0.24in	20.83	1125
m1094	i0043	1094mm	43.08in	1083mm	42.65in	6mm	0.24in	21.67	1170
m1136	i0045	1136mm	44.72in	1125mm	44.29in	6mm	0.24in	22.50	1215
m1178	i0046	1178mm	46.36in	1167mm	45.93in	6mm	0.24in	23.33	1260
m1219	i0048	1219mm	48.01in	1208mm	47.57in	6mm	0.24in	24.17	1305
m1261	i0050	1261mm	49.65in	1250mm	49.21in	6mm	0.24in	25.00	1350
m1303	i0051	1303mm	51.29in	1292mm	50.85in	6mm	0.24in	25.83	1395
m1344	i0053	1344mm	52.93in	1333mm	52.49in	6mm	0.24in	26.67	1440
m1386	i0055	1386mm	54.57in	1375mm	54.13in	6mm	0.24in	27.50	1485
m1428	i0056	1428mm	56.21in	1417mm	55.77in	6mm	0.24in	28.33	1530
m1469	i0058	1469mm	57.85in	1458mm	57.41in	6mm	0.24in	29.17	1575
m1511	i0059	1511mm	59.49in	1500mm	59.06in	6mm	0.24in	30.00	1620
m1553	i0061	1553mm	61.13in	1542mm	60.70in	6mm	0.24in	30.83	1665
m1594	i0063	1594mm	62.77in	1583mm	62.34in	6mm	0.24in	31.67	1710
m1636	i0064	1636mm	64.41in	1625mm	63.98in	6mm	0.24in	32.50	1755
m1678	i0066	1678mm	66.05in	1667mm	65.62in	6mm	0.24in	33.33	1800
m1719	i0068	1719mm	67.69in	1708mm	67.26in	6mm	0.24in	34.17	1845
m1761	i0069	1761mm	69.33in	1750mm	68.90in	6mm	0.24in	35.00	1890
m1803	i0071	1803mm	70.97in	1792mm	70.54in	6mm	0.24in	35.83	1935
m1844	i0073	1844mm	72.61in	1833mm	72.18in	6mm	0.24in	36.67	1980

LINI Glow XL R020

Length Availability List




Length Code		Fixture Length ¹		LED Strip ²		End Cap Dimension ³		Wattage (W)	Output (lm)
Metric	Imperial(US)	Metric	Imperial(US)	Metric	Imperial(US)	Metric	Imperial(US)		3000K (Test Data)
m1886	i0074	1886mm	74.25in	1875mm	73.82in	6mm	0.24in	37.50	2025
m1928	i0076	1928mm	75.89in	1917mm	75.46in	6mm	0.24in	38.33	2070
m1969	i0078	1969mm	77.53in	1958mm	77.10in	6mm	0.24in	39.17	2115
m2011	i0079	2011mm	79.17in	2000mm	78.74in	6mm	0.24in	40.00	2160

¹ Actual total overall length of light fixture (LED strip + end caps + void/wire hole)

² Actual length of PCB strip

³ Actual length of 2x end caps




Linear

LINI Glow XL R020 Options

KKDC

COVER/LENS OPTIONS


* Options are an integral part of the fixture ordering codes. Please refer to **Code Table** pages.




0 Diffused U cover
W22/H27.9mm (W0.87/H1.10")

POWER FEED OPTIONS


0300 S00X 300mm (11.81") Single no sheath tail




0300 D00X 300mm (11.81") Double no sheath tail




0300 S20X 300mm (11.81") Single no sheath IP20 connector




0300 D20X 300mm (11.81") Double no sheath IP20 connector




1000 S00X 1000mm (39.37") Single no sheath tail




1000 D00X 1000mm (39.37") Double no sheath tail



1000 S20X 1000mm (39.37") Single no sheath IP20 connector



1000 D20X 1000mm (39.37") Double no sheath IP20 connector



Key

Control Gear Power supply, sub-controllers & control systems

JB Junction box / cable connection


Linear

LINI Glow XL R020 Options





POWER FEED OPTIONS (CONTINUED)

2 Pin Female Connector



2 Pin Male Connector





MOUNTING ACCESSORIES



Note: Accessories are to be ordered separately with corresponding code shown below.




KKCP-11
Concealed clip
(allow 3 per metre/40in)
S/Steel finish
L20/W22/H28.1mm
(L0.79/W0.87/H1.11")




KKCR-01-1000 1000mm (39.37in)
KKCR-01-2000 2000mm (78.74in)
KKCR-01-3000 3000mm (118.11in)
Cable raceway*
Anodised aluminium finish
W22/H36.4mm (W0.87/H1.43")
* Cut & drilled to fit on site




KKJT-02
Joining bar* (allow 1 per join)
Anodised aluminium finish
L25mm (L0.98")
* Mounting option required with
Joining bar




POWER FEED



KKCN-01 50mm (1.97in) pair
KKCN-03 300mm (11.81in) pair
2 PIN male + female connector set



KKCN-06
2 PIN 300mm (11.81in) extension
lead



Linear

LINI Glow XL R020 Accessories

KKDÖ

KKDC CONTROL



IP20
Plastic housing
L170/W59/H29mm
(L6.69/W2.32/H1.14in)

KKDM-06 1-10V
visDIM dimmable sub-controller
(4 x 8A max @ 12-36V)



IP20
Plastic housing
L170/W53.4/H28mm
(L6.69/W2.10/H1.10in)

KKSC-05 DMX
visDIM dimmable sub-controller
(4 x 5A max @ 12-36V)



IP20
Plastic housing
L170/W59/H29mm
(L6.69/W2.32/H1.14in)

KKDL-02 DALI
visDIM dimmable sub-controller
(4 x 8A max @ 12-36V)



IP20
Plastic housing
L166/W53.4/H23mm
(L6.54/W2.10/H0.91in)

KKDL-03 DALI
visDIM dimmable sub-controller
(4 x 5A max @ 12-36V)



IP20
Plastic housing
L170/W53.4/H28mm
(L6.69/W2.10/H1.10in)

KKDL-04 DALI-2
visDIM dimmable sub-controller
(4 x 5A max @ 12-36V)

AVAILABLE PSU OPTIONS

Control Mode	PSU (Order Code)	Input Voltage AC	Output Voltage DC	Rated Output Current	Rated Power	Dim %	IP Rating
Switched	CEN-60-24	90-295V	24V	2.5A	60W	-	IP67
	HLG-60H-24	90-305V	24V	2.5A	60W	-	IP67
	HLG-100H-24	90-305V	24V	4.0A	100W	-	IP67
	HLG-150H-24	90-305V	24V	6.3A	150W	-	IP67
	HLG-240H-24	90-305V	24V	10A	240W	-	IP67
0-10V (1-10V)	PWM-40-24	90-305V	24V	1.67A	40W	100-0.15 (100-10)	IP67
	PWM-60-24	90-305V	24V	2.5A	60W	100-0.15 (100-10)	IP67
	PWM-90-24	90-305V	24V	3.67A	90W	100-0.15 (100-10)	IP67
	PWM-120-24	90-305V	24V	5.0A	120W	100-0.15 (100-10)	IP67
DALI	LIN100A1	120-277V	24V	1A per channel	100W	100-0.1	IP66/IP40
DMX RGB	LIN100A1	120-277V	24V	1.33A per channel	100W	100-0.1	IP66/IP40
DMX RGBW	LIN100A1	120-277A	24V	1A per channel	100W	100-0.1	IP66/IP40

Flicker Free Options - Combination of PSU+ sub-controller

Control Mode	PSU (Order Code)	Sub-controller (Order Code)	Input Voltage AC	Output Voltage DC	Rated Output Current	Rated Power	Dim %	IP Rating PSU/ Sub-controller
0-10V or 1-10V	CEN-60-24	KKDM-06	90-295V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-60H-24	KKDM-06	90-295V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-100H-24	KKDM-06	90-295V	24V	4.0A	100W	100-0.9	IP67/IP20
	HLG-150H-24	KKDM-06	90-295V	24V	6.3A	150W	100-0.9	IP67/IP20
	HLG-240H-24	KKDM-06	90-295V	24V	10.0A	240W	100-0.9	IP67/IP20
DALI	CEN-60-24	KKDL-02/03/04/visDIM PRO 30	90-295V	24V	2.5A	60W	100-0.1	IP67/IP20
	HLG-60H-24	KKDL-02/03/04/visDIM PRO 30	90-305V	24V	2.5A	60W	100-0.1	IP67/IP20
	HLG-100H-24	KKDL-02/03/04/visDIM PRO 30	90-305V	24V	4.0A	100W	100-0.1	IP67/IP20
	HLG-150H-24	KKDL-02/03/04/visDIM PRO 30	90-305V	24V	6.3A	150W	100-0.1	IP67/IP20
	HLG-240H-24	KKDL-02/03/04/visDIM PRO 30	90-305V	24V	10.0A	240W	100-0.1	IP67/IP20
DMX RGB	CEN-60-24	KKSC-05	90-295V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-60H-24	KKSC-05	90-305V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-100H-24	KKSC-05	90-305V	24V	4A	100W	100-0.9	IP67/IP20
	HLG-150H-24	KKSC-05	90-305V	24V	6.3A	150W	100-0.9	IP67/IP20
	HLG-240H-24	KKSC-05	90-305V	24V	10.0A	240W	100-0.9	IP67/IP20

¹ The items shown above cover the most frequently used specification but does not exhaust the possible options

² PSU and/or driver can be chosen from the table, or KKDC may recommend the best option upon receipt of the controls requirement and installation environment

³ Electrical shop drawing will include detailed information of PSU and relevant control drivers

⁴ Cut sheets are available on the controls section of www.kkdc.lighting or upon request